

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) Nr. 305/2011 (Construction Products Regulation)

Nr. Bistal-DoP-004-13/EN

1.Product type:	Bistal bed joint reinforcemen type Bi 56 ob – Quality 700	t of welded steel wire meshwork,
2.Type identification of the construction product:	Type and article number displayed on the packaging	
3.Intended use of the product	t: Welded wire meshwork - ladder type, bed joint reinforcement in masonry for structural applications.	
4.Manufacturer:	Bistål AB i Västervik, Fridkullagatan 5, SE- 593 62 Västervik	
5.System of assessment and verification of performance:	System 3	
6.Harmonized standard:	EN-845-3:2013 Notified body No. 0402, SP Technical Research Institute of Sweden has performed initial type testing (ITT) of the product according to the standard.	
7.Declared performance:		
	Dimensions	Limit deviations
Length (I)	4 000 mm	+/- 1,5 %
Width (a)	32 mm	+/- 5 mm
Profile height (t)		
	5,6 mm	+/- 0,4 mm
Wire size (c)	5,6 mm 5,6 mm	+/- 0,4 mm +/- 0,1 mm
Wire size (c) Wire size (d)		
	5,6 mm	+/- 0,1 mm
Wire size (d) Pitch of wires (b) Essential characteristics	5,6 mm 3,5x5,5 mm	+/- 0,1 mm +/- 0,1 mm
Wire size (d) Pitch of wires (b) Essential characteristics Coating reference	5,6 mm 3,5x5,5 mm 95 mm Performance data NPD	+/- 0,1 mm +/- 0,1 mm +/- 3 % Harmonized technical specification
Wire size (d) Pitch of wires (b) Essential characteristics Coating reference Shear load capacity	5,6 mm 3,5x5,5 mm 95 mm Performance data NPD 9,4 kN	+/- 0,1 mm +/- 0,1 mm +/- 3 % Harmonized technical specification EN-845-3 + FPC
Wire size (d) Pitch of wires (b) Essential characteristics Coating reference Shear load capacity Characteristic yield strength o	5,6 mm 3,5x5,5 mm 95 mm Performance data NPD 9,4 kN	+/- 0,1 mm +/- 0,1 mm +/- 3 % Harmonized technical specification EN-845-3 + FPC EN-845-3 – ITT by notified body
Wire size (d) Pitch of wires (b) Essential characteristics Coating reference Shear load capacity Characteristic yield strength o Bond strength	5,6 mm 3,5x5,5 mm 95 mm Performance data NPD 9,4 kN of wires 690 N/mm2 6,48 kN	+/- 0,1 mm +/- 0,1 mm +/- 3 % Harmonized technical specification EN-845-3 + FPC EN-845-3 – ITT by notified body EN-845-3 – ITT by notified body
Wire size (d) Pitch of wires (b) Essential characteristics Coating reference Shear load capacity Characteristic yield strength o	5,6 mm 3,5x5,5 mm 95 mm Performance data NPD 9,4 kN of wires 690 N/mm2	+/- 0,1 mm +/- 0,1 mm +/- 3 % Harmonized technical specification EN-845-3 + FPC EN-845-3 – ITT by notified body EN-845-3 – ITT by notified body

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Västervik July 1, 2013